



Vandal Shield Option
Cat.# WP106VS

Wire Guard Option
Cat.# WP106WG

Visor Option
Cat.# WP106V



Application: Ideal for parking areas, entrances, walkways, underpasses, loading docks and tunnels.

Specifications

Housing: Heavy duty die cast aluminum construction with corrosion resistant hardware. See finish note.

Door Frame: Heavy duty die cast aluminum, one piece silicone gasket, seals door frame to housing. See finish note.

Lens: Impact resistant borosilicate glass, silicone caulked to door frame.

Reflector: Anodized aluminum, designed for maximum efficiency.

Ballast: Pre-wired C.W.A., H.P.F. core and coil with capacitor.

Lamp: Clear medium base, (by others).

Lamp Holder: High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact, lamp grips, SF-2 leads (200° C). Impregnated gasket.

Finish: Dark Bronze, detergent cleaned, prime coated. Chip resistant powder urethane polyester coating, electrostatic applied and baked.

Photometric Information: Contact factory.

Labels: U/L, CU/L listed suitable for wet location. I.B.E.W. labeled.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Ordering Information

Catalog Number	Watts	Light Source
GSM10612	50	HPS
GSM10613	70	HPS
GSM10614	100	HPS
GSM10615	150	HPS
GSM10622	50	MH
GSM10623	70	MH
GSM10624	100	MH
GSM10625	150	MH
GSM10626	175	MH