



**Application:** Ideal for parking areas, entrances, walkways, underpasses, loading docks and recreation areas.

### Specifications

**Housing:** Heavy duty polycarbonate with corrosion resistant hardware. Dark bronze

**Lens:** Impact resistant polycarbonate with silicone rubber gasket.

**Reflector:** Anodized aluminum, designed for maximum efficiency.

**Ballast (HID):** Pre-wired C.W.A., H.P.F. core and coil with capacitor.

**Ballast (CF):** H.P.F. electronic class P 120V—277V.

**Lamp (HID):** Clear medium base, (by others).

**Lamp (CF):** PLT26W, 32W or 42W (by others).

**Lamp Holder (HID):** High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact, lamp grips, SF-2 leads (200? C). Impregnated gasket.

**Lamp Holder (CF):** 26W and 32W GX24q-3 42W GX24q-4.

**Photometric Information:** Contact factory.

**Labels:** U/L, CU/L listed suitable for wet location. I.B.E.W. labeled.

*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE*

### Ordering Information

Catalog Number	Watts	Light Source
GSM35212*	50	HPS
GSM35213*	70	HPS
GSM352T3	PLT-26	CF
GSM352T4	PLT-32	CF
GSM352T5	PLT-42	CF

\*120V only.