



Vandal Shield Option
 Cat.# WP704VS

Wire Guard Option
 Cat.# WP704WG

Visor Option
 Cat.# WP704V



Application: Ideal for parking areas, entrances, walkways, underpasses, loading docks and tunnels.

Specifications

Housing: Heavy duty die cast aluminum construction with corrosion resistant hardware. See finish note.

Door Frame: Heavy duty die cast aluminum, one piece silicone gasket, seals door frame to housing. See finish note.

Lens: Impact resistant borosilicate glass, silicone caulked to door frame.

Reflector: Anodized aluminum, designed for maximum efficiency.

Ballast: Pre-wired C.W.A., H.P.F. core and coil with capacitor.

Lamp: Clear medium base, (by others).

Lamp Holder: High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact, lamp grips, SF-2 leads (200° C). Impregnated gasket.

Finish: Dark Bronze, detergent cleaned, prime coated. Chip resistant powder urethane polyester coating, electrostatic applied and baked.

Photometric Information: Contact factory.

Labels: U/L, CU/L listed suitable for wet location. I.B.E.W. labeled.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Ordering Information

Catalog Number	Watts	Light Source
GSM70412	50	HPS
GSM70413	70	HPS
GSM70414	100	HPS
GSM70415*	150	HPS
GSM70422	50	MH
GSM70423	70	MH
GSM70424	100	MH

*120V only.