


Wire Guard Option
Cat.# WP708WG



Visor Option
Cat.# WP708V



Application: Ideal for parking areas, entrances, walkways, underpasses, loading docks and tunnels.

Specifications

Housing: Heavy duty die cast aluminum construction with corrosion resistant hardware. See finish note.

Door Frame: Heavy duty die cast aluminum, one piece silicone gasket, seals door frame to housing. See finish note.

Lens: Impact resistant borosilicate glass, silicone caulked to door frame.

Reflector: Anodized aluminum, designed for maximum efficiency.

Ballast: Pre-wired C.W.A., H.P.F. core and coil with capacitor.

Lamp: Clear mogul base, (by others).

Lamp Holder: High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact, lamp grips, SF-2 leads (200? C). Impregnated gasket.

Finish: Dark Bronze, detergent cleaned, prime coated. Chip resistant powder urethane polyester coating, electrostatic applied and baked.

Photometric Information: Contact factory.

Labels: U/L, CU/L listed suitable for wet location. I.B.E.W. labeled.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Ordering Information

Catalog Number	Watts	Light Source
GSM70817	250	HPS
GSM70818	400	HPS
GSM70827	250	MH
GSM708225	250	MH <small>PULSE START</small>
GSM708232	320	MH <small>PULSE START</small>
GSM708235	350	MH <small>PULSE START</small>
GSM70828	400	MH
GSM708240	400	MH <small>PULSE START</small>