



**Application:** Ideal for parking areas, entrances, walkways, underpasses, loading docks and tunnels.

### Specifications

- Housing:** Heavy duty die cast aluminum construction with corrosion resistant hardware. See finish note.
- Door Frame:** Heavy duty die cast aluminum, one piece silicone gasket, seals door frame to housing. See finish note.
- Lens:** Impact resistant borosilicate glass lens, silicone caulked to door frame.
- Reflector:** Anodized aluminum, designed for maximum efficiency.
- Ballast:** Pre-wired C.W.A., H.P.F. core and coil with capacitor.
- Lamp:** Clear mogul base, (by others).
- Lamp Holder:** High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact, lamp grips, SF-2 leads (200? C). Impregnated gasket.
- Finish:** Dark Bronze, detergent cleaned, prime coated. Chip resistant powder urethane polyester coating, electrostatic applied and baked.
- Photometric Information:** Contact factory.
- Labels:** U/L, CU/L listed suitable for wet location. I.B.E.W. labeled.

*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE*

### Ordering Information

Catalog Number	Watts	Light Source
GSM72715	150	HPS
GSM72717	250	HPS
GSM72718	400	HPS
GSM72726	175	MH
GSM72727	250	MH
GSM727225	250	MH <small>PULSE START</small>
GSM727232	320	MH <small>PULSE START</small>
GSM727235	350	MH <small>PULSE START</small>
GSM72728	400	MH
GSM727240	400	MH <small>PULSE START</small>