



609T Series
Compact Fluorescent Vertical Lamp
10" Diameter Aluminum Cylinder
Surface, Pendant or Wall Mount

Specifications

Cylinder

.080" Aluminum, rolled and seam welded. See finish note.

Reflector

Spun aluminum #3002, polished to a mirror finish then electro-chemically processed to provide specular Alzak* finish.

Reflector Top

Extruded aluminum, supports socket and reflector. Dissipates heat from lamp and socket.

Ballast

Compact fluorescent electronic high power factor class P, universal voltage 120 thru 277 volt; 50/60 Hz.

Lamp

Compact fluorescent PLT lamp max. 57W, 4 pin base (by others).

Lamp Holder

Vertically mounted white thermoplastic with snap-in lamp retainer springs. See table.

Mounting Pan (Surface & Pendant Mount)

Cast aluminum with 3/4" inner collar, finished to match cylinder housing.

Mounting Strap (Surface Mount)

Painted steel, mounts directly to outlet box. Supports pan with 1/4-20 studs and wing nuts.

Canopy Set (Pendant Mount)

0-45° hang straight for 3/8" I.P. Finished to match housing.

Wall Bracket (Wall Mount)

One-piece cast aluminum bracket/arm assembly with access plate for wire inspection. Cast aluminum, wall mounting plate with 1/4" thick neoprene gasket. Quick disconnect wiring harness. Finished to match housing.

Finish

Detergent cleaned with iron phosphate and chromic acid rust inhibitor. Chip resistant powder urethane polyester coating, electro-static applied and baked. Standard colors black, white and bronze. Custom colors are available. Consult factory or sales representative.

Labels

U/L, CU/L listed & I.B.E.W labeled; flush and pendant mount suitable for damp location, wet location for wall mount.

Photometric Information Contact factory.

*ALZAK is a registered Trademark of the Aluminum Company of America.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



3254 North Kilbourn Avenue Chicago, Illinois 60641 02-09-04
 Phone 773-427-7000 Fax 800-217-1260 www.escolighting.com





609T Series

Compact Fluorescent Vertical Lamp

10" Diameter Aluminum Cylinder

Surface, Pendant or Wall Mount

Catalog Numbers Lens / Aperture Options

Architectural open
downlight.



Surface Mount	Watts	Lamp Base
S609T3	26W	GX24q-3
S609T4	32W	GX24q-3
S609T5	42W	GX24q-4
S609T6	57W	GX24q-5

C#73 Tempered prismatic glass
lens.



Surface Mount	Watts	Lamp Base
S629T3	26W	GX24q-3
S629T4	32W	GX24q-3
S629T5	42W	GX24q-4

C#73 Prismatic tempered glass
lens and splayed stepped baffle.



Surface Mount	Watts	Lamp Base
S659T3	26W	GX24q-3
S659T4	32W	GX24q-3
S659T5	42W	GX24q-4

C#73 Prismatic tempered glass
lens and splayed baffle.



Surface Mount	Watts	Lamp Base
S689T3	26W	GX24q-3
S689T4	32W	GX24q-3
S689T5	42W	GX24q-4

Architectural open downlight
with baffle.



Surface Mount	Watts	Lamp Base
S619T3	26W	GX24q-3
S619T4	32W	GX24q-3
S619T5	42W	GX24q-4
S619T6	57W	GX24q-5

Flat fresnel glass lens.



Surface Mount	Watts	Lamp Base
S639T3	26W	GX24q-3
S639T4	32W	GX24q-3
S639T5	42W	GX24q-4

Fresnel glass lens and splayed
stepped baffle.



Surface Mount	Watts	Lamp Base
S669T3	26W	GX24q-3
S669T4	32W	GX24q-3
S669T5	42W	GX24q-4

Fresnel glass lens and splayed
baffle.



Surface Mount	Watts	Lamp Base
S699T3	26W	GX24q-3
S699T4	32W	GX24q-3
S699T5	42W	GX24q-4


Options & Accessories



Pendant mount
Suffix catalog num-
ber with Pxx. xx=
Stem length in
inches.
Example: P24 =
canopy set with 24"
stem.



Cast aluminum
wall mount.
Change S in
catalog number
to W.



Louver guard option.
Suffix catalog number
with LG3.




Photo
Control
Option
Suffix
Catalog #
With

PC4 120 Volt
PC5 277 Volt



Fuse and Fuse Holder
Suffix Catalog
Number With "F"

Standard Colors
Suffix Catalog
Number With
W= White
BZ= Bronze
BL= Black