



Application: Highways, city streets, parking lots, commercial and industrial complexes, residential areas, parkway lighting and other general applications

Specifications

Housing: Heavy duty die cast aluminum construction with corrosion resistant hardware. 4 bolt leveling slip fitter mount. See finish note.

Door Frame: Heavy duty die cast aluminum, one piece silicone gasket, seals door frame to housing. See finish note.

Lens: Impact resistant borosilicate glass refractor, silicone caulked to door frame.

Reflector: Anodized aluminum, designed for maximum efficiency.

Ballast: Pre-wired C.W.A., H.P.F. core and coil with capacitor.

Lamp: Clear mogul base, (by others).

Lamp Holder: High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact, lamp grips, SF-2 leads (200° C). Impregnated gasket.

Finish: Silver, detergent cleaned, prime coated. Chip resistant powder urethane polyester coating, electrostatic applied and baked.

Photometric Information: Contact factory.

Labels: U/L, CU/L listed suitable for wet location. I.B.E.W. labeled.

Ordering Information

Catalog Number	Watts	Light Source
GRW4R15	150	HPS
GRW4R17	250	HPS
GRW4R18	400	HPS
GRW4R26	175	MH
GRW4R27	250	MH
GRW4R225	250	MH PULSE START
GRW4R232	320	MH PULSE START
GRW4R235	350	MH PULSE START
GRW4R28	400	MH
GRW4R240	400	MH PULSE START

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE