



Application: Ideal for parking garages, entrances, walkways, underpasses, loading docks, recreation areas and other general applications.

Specifications

Housing: Heavy duty die cast aluminum with tapped holes on both sides for power supply entry. White powder coated finish. See finish note.

Door Frame: Heavy duty die cast aluminum, one piece silicone gasket, seals door frame to housing, two stainless steel thumb latches for entry, two stainless steel hinges. See finish note.

Lens: Cast borosilicate prismatic glass refractor, silicone caulked to frame.

Reflector: One piece anodized aluminum, designed in conjunction with the lens for efficiency.

Ballast: Pre-wired C.W.A., H.P.F. core and coil with capacitor.

Lamp: Clear lamp (by others). See table.

Lamp Holder: High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact, lamp grips, SF-2 leads (200° C). Impregnated gasket.

Finish: White, detergent cleaned, prime coated. Chip resistant powder urethane polyester coating, electrostatic applied and baked.

Photometric Information: Contact factory.

Labels: U/L, CU/L listed suitable for wet location. I.B.E.W. labeled.

ORDERING INFORMATION

Catalog No.	Wattage	Light Source	Lamp Base
GSM01915	150	HPS	Medium
GSM01917	250	HPS	Mogul
GSM01918	400	HPS	Mogul
GSM019217	175	MH PULSE START	Medium
GSM019220	200	MH PULSE START	Medium
GSM019225	250	MH PULSE START	Mogul
GSM019232	320	MH PULSE START	Mogul
GSM019235	350	MH PULSE START	Mogul
GSM019240	400	MH PULSE START	Mogul

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE