



**Application:** Ideal for parking garages, entrances, walkways, loading docks, recreation areas and other general applications.

### Specifications

**Housing:** Heavy duty die cast aluminum with quick mount system. White powder coated finish.

See finish note.

**Lens:** Injection molded acrylic lens computer designed for wide distribution pattern, gasketed to frame.

**Reflector:** One piece anodized aluminum, designed in conjunction with the lens for efficiency.

**Ballast:** Pre-wired C.W.A., H.P.F. core and coil with capacitor.

**Lamp:** Clear med. Base **open rated** lamp (by others).

**Lamp Holder:** High heat 4 K.V. rated, w/nickel plated copper screw shell, spring loaded center contact, lamp grips, SF-2 leads (200°C). Impregnated gasket.

**Finish:** White, detergent cleaned, prime coated. Chip resistant powder urethane polyester coating, electrostatic applied and baked.

**Photometric Information:** Contact factory.

**Labels:** U/L, CU/L listed suitable for wet location, under covered ceiling applications.

I.B.E.W. labeled.

*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE*

Catalog Number	Watts	Light Source
GSM02313	70	HPS
GSM02314	100	HPS
GSM02315	150	HPS
GSM02323	70	MH
GSM02324	100	MH
GSM02325	150	MH
GSM023217	175	MH PS