

SFLB16 Series 16" Surface Mount Outdoor Area Floodlight Fulham High Horse Induction Lamp System





SPECIFICATIONS

Housing: Die cast aluminum with internal rib design to prevent wall distortion or stress sagging; built-in hinge. External 16GA. Mounting flange provided with (4) 1/2" by 3/4" mounting holes for fixture installation. Housing shall have penetration from external junction box to the ballast compartment sealed with weather-proof wire connector (connector shall have individual holes in grommet for each wire). Finished architectural bronze. See finish note.

Door Assembly: Die cast aluminum, clear tempered lens, silicone caulked to frame plus eight hold down clips, integral silicone door frame gasket to complete lifetime seal. Finished architectural bronze. See finish note.

Reflector: Computer generated one-piece semispecular aluminum for maximum efficiency.

Ballast: High frequency electronic ballast 100W or 120—277V. Contact factory for other voltages.

Lamp: Fulham High Horse electrodeless fluorescent lamp with average rated life of 100,000 hours.

Finish: Detergent cleaned with iron phosphate and chromic acid rust inhibitor, resistant chip resistant powder urethane polyester coating, electrostatic applied and baked. Standard colors textured black, sky white and textured bronze. Custom colors are available. Consult factory or sales representative.

Labels: I.B.E.W. labeled, ETL / CETL listed. Suitable for wet location.


Fixture Warranty: The mechanics are guaranteed to be free from defective material and workmanship, under normal installation and operating conditions, for five years from date of shipment from the factory. See general terms and conditions.


Maximum Ambient Temperature: Maximum 118°F. **Photometric Information:** Contact factory.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



DIMENSIONS







WBE City of Chicago Certified

3254 North Kilbourn Avenue Chicago, Illinois 60641-4505 Phone: 773-427-7000 Fax: 800-217-1260 www.escolighting.com Established 1975

g





SFLB16 Series 16" Surface Mount Outdoor Area Floodlight Fulham High Horse Induction Lamp System



HOW TO ORDER





Catalog Number SFLBF105016

Lamps 85W 100W

Initial Lumens 5,950 7,000

Ballast 85W 100W

Color Temp 5000 5000

EXAMPLE ORDER NUMBER: SFLBF85016= Fulham induction 85 watt lamp, 5000k.

ACCESSORIES











