



Municipality 6000 / 7000 Series

Indoor / Outdoor Cylinder Wall, Surface or Pendant Mount Philips QL Induction Lamp

Specifications

Cylinder Housing: Rolled and seam welded aluminum .080" thick. See finish note.

Reflector: Spun aluminum #3002, polished to mirror finish then electro-chemically processed to provide specular Alzak* finish.

Lens: Corning #73 prismatic tempered glass lens.

Baffle: One-piece spun aluminum finished matte black.

Ballast: Philips QL induction high frequency electronic ballast. 165W Operating in a range of 200 to 277 volts, 55W and 85W 120 volt, 50 or 60 Hz. Contact factory for other voltages.

Lamp: Philips QL induction electrodeless fluorescent lamp with average rated life 100,000 hours.

Mounting Pan: Cast aluminum with 3/4" inner collar 16" dia., 3/8" inner collar 10" dia. with steel mounting strap to mount directly to outlet box. Supports pan with 1/4 x 20 threaded studs and wing nuts. Finished to match cylinder housing.

Canopy Set: 16" diameter cylinder 0-45° hang straight for 3/4" I.P., 10" diameter cylinder 0-45° hang straight for 3/8" I.P. Stem and canopy finished to match housing, pendant mount.

Wall Bracket: One-piece cast aluminum bracket/arm assembly with access plate for wire inspection. Cast aluminum, wall mounting plate with 1/4" thick neoprene gasket. Quick disconnect wiring harness. Finished to match cylinder.

Finish: Detergent cleaned with iron phosphate and chromic acid rust inhibitor. Chip resistant powder urethane polyester coating, electrostatic applied and baked. Custom colors are available. Consult factory or sales representative.

Labels: I.B.E.W., U/L listed; surface and pendant mount suitable for damp location, wet location for wall mount.

Photometric Information: Contact factory.

*ALZAK is a registered Trademark of the Aluminum Company of America

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



HOW TO ORDER: Use the table below to choose the 6000 or 7000 series fixture of your choice. Select a number from each list that corresponds to a specific feature unique to your desired requirements.

EXAMPLE: S6080P224BL = Pendant mount, open aperture, 85W QL induction lamp, textured black with 24" stem.

Mounting System	Cylinder Diameter	Aperture	Wattage QL Induction Lamp	Color
S=Surface mount	6= 10" 7= 16"	0=Open 1=Open with Baffle. 2=C73 prismatic glass lens.	7=55W Induction lamp 3500 lumens. 8=85W induction lamp 6000 lumens. 9=165W induction lamp 12000 lumens 16" Dia. only.	BZ=Textured Bronze BL=Textured Black W=Sky White SD=Silver Other Consult Factory

Pendant mount suffix catalog number with:
P1x=16" dia. Cylinder.
P2x=10" dia. Cylinder.
 (x = required stem length in inches).



DIMENSIONAL INFORMATION

