

ITL Test Report #E27704B. IES

Catalogue Number R10232 / RS10232
C73 Prismatic Glass Lens
Luminaire: Recessed 2' x 2' Lay-In
Lamp: Phosphor coated 320-Watt Metal Halide, Pulse Start
Rated at 27500 lumens
Mounting: Recessed

TILT=NONE

1	27900	.87	19	9	1	1	1.75	1.75	0										
1	1	455																	
0	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
0	22.5	45	67.5	90	112.5	135	157.5	180											
9760	9760	9650	9540	9320	8850	8110	7090	6070	4730	3440	2220	1530	1200	880	660	490			
310	0																		
9760	9720	9660	9500	9170	8660	8070	7080	5740	4590	3520	2580	1670	1170	840	620	470			
230	0																		
9760	9740	9650	9560	9280	8890	8400	7690	6520	4970	3520	2550	1990	1420	940	670	500			
230	0																		
9760	9730	9670	9560	9380	9050	8550	7730	6490	5300	3920	2920	1960	1340	890	720	490			
230	0																		
9760	9730	9690	9600	9400	9060	8450	7640	6380	5110	3860	2820	1880	1240	920	740	520			
250	0																		
9760	9740	9670	9580	9380	9080	8530	7700	6640	5250	4070	3150	2150	1360	920	750	560			
270	0																		
9760	9740	9640	9540	9330	9050	8570	7780	6880	5370	3870	2920	2230	1540	1030	740	540			
290	0																		
9760	9720	9630	9510	9270	8920	8330	7590	6420	5260	4020	2920	1970	1380	980	720	560			
320	0																		
9760	9710	9590	9450	9120	8620	7860	7070	5840	4480	2990	2000	1620	1140	850	650	450			
180	0																		