

27704. IES

ITL Test Report #27704 - Catalogue Number R1028

Luminaire: Recessed 2' x 2' Lay-In

Lamp: Phosphor coated 400-Watt Metal Halide, MH400C/HOR  
Rated at 32,000 lumens

Mounting: Recessed

TILT=NONE

1.0	32000.0	1.0	19.0	9.0	1.0	1.0	1.75	1.75	0.0											
1.0	1.0	455.0																		
0.0	5.0	10.0	15.0	20.0	25.0	30.0	35.0	40.0	45.0											
50.0	55.0	60.0	65.0	70.0	75.0	80.0	85.0	90.0												
0.0	22.5	45.0	67.5	90.0	112.5	135.0	157.5	180.0												
9760.0	9760.0	9650.0	9540.0	9320.0	8850.0	8110.0	7090.0	6070.0												
4730.0	3440.0	2220.0	1530.0	1200.0	880.0	660.0	490.0	310.0	0.0											
9760.0	9720.0	9660.0	9500.0	9170.0	8660.0	8070.0	7080.0	5740.0												
4590.0	3520.0	2580.0	1670.0	1170.0	840.0	620.0	470.0	230.0	0.0											
9760.0	9740.0	9650.0	9560.0	9280.0	8890.0	8400.0	7690.0	6520.0												
4970.0	3520.0	2550.0	1990.0	1420.0	940.0	670.0	500.0	230.0	0.0											
9760.0	9730.0	9670.0	9560.0	9380.0	9050.0	8550.0	7730.0	6490.0												
5300.0	3920.0	2920.0	1960.0	1340.0	890.0	720.0	490.0	230.0	0.0											
9760.0	9730.0	9690.0	9600.0	9400.0	9060.0	8450.0	7640.0	6380.0												
5110.0	3860.0	2820.0	1880.0	1240.0	920.0	740.0	520.0	250.0	0.0											
9760.0	9740.0	9670.0	9580.0	9380.0	9080.0	8530.0	7700.0	6640.0												
5250.0	4070.0	3150.0	2150.0	1360.0	920.0	750.0	560.0	270.0	0.0											
9760.0	9740.0	9640.0	9540.0	9330.0	9050.0	8570.0	7780.0	6880.0												
5370.0	3870.0	2920.0	2230.0	1540.0	1030.0	740.0	540.0	290.0	0.0											
9760.0	9720.0	9630.0	9510.0	9270.0	8920.0	8330.0	7590.0	6420.0												
5260.0	4020.0	2920.0	1970.0	1380.0	980.0	720.0	560.0	320.0	0.0											
9760.0	9710.0	9590.0	9450.0	9120.0	8620.0	7860.0	7070.0	5840.0												
4480.0	2990.0	2000.0	1620.0	1140.0	850.0	650.0	450.0	180.0	0.0											